Maintenance products

Plain bearings Linear technology



SCHAEFFLER

MAINTENANCE PRODUCTS Hydraulic Nuts – precise mounting of conical rolling bearings



Product characteristics

- Easy to install and remove
- Bore for the dial gauge in the press ring
- Visual display of the maximum stroke by means of a red O-ring
- Marking of the max. pressure and thread
- Piston can be easily removed to replace the seals

Customer benefits

- Precise mounting of the bearing by means of precise measurement of the displacement and display on the dial gauge
- A measurement and test report is included in the scope of delivery
- Marking of the max. stroke
- Comprehensive product series
- Maintenance-friendly

Applications

- Mounting and dismounting of rolling bearings with tapered bore
- Mounting and dismounting of components such as couplings, gears and ships' propellers

Available types

• HYDNUT-E

Standard design with a metric fine-pitch or trapezoidal thread, which fits all standardized adapter and withdrawal sleeves with metric dimensions.

Standard series from HYDNUT50-E to HYDNUT1180-E

• HYDNUT-E-INCH

Special design with an inch thread that meets the ABMA standards. Inch series from HYDNUT50-E-INCH to HYDNUT950-E-INCH

• HYDNUT-HEAVY

Heavy-duty design specifically developed for high press-on forces. HYDNUT100-HEAVY to HYDNUT900-HEAVY

• HYDNUT special design Special design for customer-specific applications, e.g. F-625947.HYDNUT • HYDNUT displacement measuring devices Analog dial gauge with 2 HYDNUT.GAUGE-ANALOG extension pieces Digital dial gauge with 2 HYDNUT.GAUGE-DIGITAL extension pieces

Detailed information can be found in the TPI 196 technical product information.



Schaeffler Technologies AG & Co. KG

Georg-Schäfer-Straße 30 97421 Schweinfurt Germany Phone +49 9721 91-0 E-mail industrial-services@schaeffler.com Every care has been taken to ensure the correctness of the information contained in this publication but no liability can be accepted for any errors or omissions. We reserve the right to make technical changes.

© Schaeffler Technologies AG & Co. KG Issued: 2018, November

This publication or parts thereof may not be reproduced without our permission.